



Faro LED

Floodlighting



Architectural Floodlight available with multiple beam options. Also available in mast version (see separate leaflet).

Construction: Aluminium housing. IP65. IK07. Stainless Fixings.

Lens: Clear tempered glass as standard. Other types on request.

Finish: Light Grey RAL 9006 as standard. Dark Grey on request.

LED: Available in 7w-47w LED. 4K as standard, 3K on request.

Optics: 6 Beam Angles available: 14° Spot to 62° Flood. Medium (24°) beam as standard.


Driver: Internal LED driver.


Options: DALI, beam angles, RAL colours on request, Anti-glare louver, Nylon stake. Anti vandal Screen, Microprismatic lens, and Directional flaps on size 3 only.



Manufactured: EU.

Product Compliance: EN 60598; CE.







Mast version



Size 3




Directional Flaps




Nylon Stake

DIMENSIONS


Size 1



Size 2



Size 3



All dimensions in mm.



Flat version (on request)

ORDERING CODE

Wattage	Type	Size	Code	Description	*Lumens
7w	LED	1	G1132.AHST400	Faro Floodlight, 15° Beam, 4K	885 lm
7w	LED	1	G1132.AHFT400	Faro Floodlight, 32° Beam, 4K	885 lm
16w	LED	2	G1133.LRST400	Faro Floodlight, 14° Beam, 4K	1997 lm
16w	LED	2	G1133.LRMT400	Faro Floodlight, 22° Beam, 4K	1997 lm
16w	LED	2	G1133.LRFT400	Faro Floodlight, 35° Beam, 4K	1997 lm
29w	LED	2	G1133.FNST400	Faro Floodlight, 14° Beam, 4K	3401 lm
29w	LED	2	G1133.FNMT400	Faro Floodlight, 22° Beam, 4K	3401 lm
29w	LED	2	G1133.FNFT400	Faro Floodlight, 35° Beam, 4K	3401 lm
32w	LED	3	G1107.ECST400	Faro Floodlight, 16° Beam, 4K	3397 lm
32w	LED	3	G1107.ECMT400	Faro Floodlight, 30° Beam, 4K	3397 lm
32w	LED	3	G1107.ECFT400	Faro Floodlight, 62° Beam, 4K	3397 lm
39w	LED	3	G1107.CDST400	Faro Floodlight, 16° Beam, 4K	4675 lm
39w	LED	3	G1107.CDMT400	Faro Floodlight, 30° Beam, 4K	4675 lm
39w	LED	3	G1107.CDFT400	Faro Floodlight, 62° Beam, 4K	4675 lm
47w	LED	3	G1107.FLST400	Faro Floodlight, 16° Beam, 4K	5606 lm
47w	LED	3	G1107.FLMT400	Faro Floodlight, 30° Beam, 4K	5606 lm
47w	LED	3	G1107.FLFT400	Faro Floodlight, 62° Beam, 4K	5606 lm

* Source Lumens

OPTIONS

3K: 3000K, Colour Temperature
.19: Light Grey Finish
.05: Dark Grey Finish
DALI: DALI on request
STK: Nylon Stake
GLA: Anti-glare louvre
GAC181: Anti vandal screen (size 3)
GAC182: Microprismatic lens (size 3)
GAC185: Directional Flaps (size 3)