

Faro Mast

Floodlighting







Architectural floodlight array available in a range of LED wattages, beam types and floodlight accessories.

Column Construction:
Galvanised Steel, Constant Diameter with Painted Finish (Flanged or Rooted). Typical Height 4m-8m with an array of Floodlights (2/4/6/8 etc) as required.

Luminaire Construction:
Aluminium. IP65. IK08. Internal Driver.

Lens: Clear tempered glass as standard. Other types on request.

Finish: Grey RAL 9006 as standard. Dark Grey on request.

LED: Available in 7w-46w LED. 4000K as standard, 3000K on request.

Optics: Narrow, Medium or Wide Beam options. Medium Beam as standard.

Options: DALI, beam angles, RAL, Anti-glare louver, Anti vandal Screen, Microprismatic lens, Directional flaps.

Manufactured: EU.

Product Compliance: EN 60598; CE.

VeeLite




Size 1



Size 2




Size 3




Directional Flaps

DIMENSIONS


Size 1



Size 2



Size 3



All dimensions in mm.



ORDERING CODE

Wattage	Type	Size	Code	Description	*Lumens
7w	LED	1	G1132.AHST400	Faro Floodlight, 17° Beam, 4K	1043 lm
7w	LED	1	G1132.AHFT400	Faro Floodlight, 32° Beam, 4K	1043 lm
16w	LED	2	G1133.LRST400	Faro Floodlight, 14° Beam, 4K	2345 lm
16w	LED	2	G1133.LRMT400	Faro Floodlight, 22° Beam, 4K	2345 lm
16w	LED	2	G1133.LRFT400	Faro Floodlight, 35° Beam, 4K	2345 lm
29w	LED	2	G1133.FNST400	Faro Floodlight, 14° Beam, 4K	4022 lm
29w	LED	2	G1133.FNMT400	Faro Floodlight, 22° Beam, 4K	4022 lm
29w	LED	2	G1133.FNFT400	Faro Floodlight, 35° Beam, 4K	4022 lm
25w	LED	3	G1107.CGST400	Faro Floodlight, 16° Beam, 4K	3698 lm
25w	LED	3	G1107.CGMT400	Faro Floodlight, 29° Beam, 4K	3698 lm
25w	LED	3	G1107.CGFT400	Faro Floodlight, 72° Beam, 4K	3698 lm
32w	LED	3	G1107.ECST400	Faro Floodlight, 16° Beam, 4K	4689 lm
32w	LED	3	G1107.ECMT400	Faro Floodlight, 29° Beam, 4K	4689 lm
32w	LED	3	G1107.ECFT400	Faro Floodlight, 72° Beam, 4K	4689 lm
46w	LED	3	G1107.FLST400	Faro Floodlight, 16° Beam, 4K	6126 lm
46w	LED	3	G1107.FLMT400	Faro Floodlight, 29° Beam, 4K	6126 lm
46w	LED	3	G1107.FLFT400	Faro Floodlight, 72° Beam, 4K	6126 lm

+ Mast (Constant Diameter column) - please specify - height - rooted/flanged - qty of Luminaires per Mast.

* Source Lumens

OPTIONS

- 3K: 3000K Colour Temperature
- .05: Dark Grey Finish
- .19: Light Grey Finish
- DALI: DALI on request
- G-125: Directional Flaps
- GAC180: Anti-glare louvre (size 3)
- GAC181: Anti vandal screen (size 3)
- GAC182: Microprismatic lens (size 3)
- GAC185: Directional Flaps (size 3)

