



Compact Series LED Bollard

External lighting



LED Bollard offered in 2 different heights.
Suitable for paths, gardens or plaza
areas.

Construction: Extruded Aluminium body.
0.5m high as standard (0.3m on Mini).
IP65 IK08.

Lens: Opal ribbed 5mm tempered glass
lens with silkscreen border,

Installation: Flanged as standard.
Stainless Steel J Bolts offered.

Finish: Light Grey RAL 9006 as standard.
Dark Grey on request.





Wattages: 12w, 4K as standard.
Asymmetric distribution. 3K on request.

Manufactured: EU.

Product Compliance: EN 60598; CE,
UKCA.

Veelite

DIMENSIONS



ORDERING CODE

Wattage	Type	Code	+J Bolts	Height	Details	*Lumens
12w	LED-3K	G1426.CAFT300	GAC274	300mm	Mini-Version, 3K.	1469 lm
12w	LED-4K	G1426.CAFT400	GAC274	300mm	Mini-Version, 4K.	1492 lm
12w	LED-3K	G1427.CAFT300	GAC274	500mm	Standard, 3K.	1469 lm
12w	LED-4K	G1427.CAFT400	GAC274	500mm	Standard, 4K.	1492 lm

* Source Lumens

OPTIONS

.05: Dark Grey Finish
.19: Light Grey Finish