



Fullonia Series

External Lighting



Architecturally designed outdoor luminaire available in suspended and post top versions.

Construction: Made up of three parts -
The Dome: Spun aluminium.
The Frame: 4 cast aluminium arms attached to base piece.
The Optical Block: Anodised aluminium reflector sealed in a clear acrylic bowl IP66 rated. IK10.

Installation: Standard Version is Post top mounted via 60mm diameter spigot/column. Optional Pendant version is mounted via a selection of special mounting brackets.

Finish: Black as standard. Other colours available on request.


LED: 54w, 77w or 108w LED. 4K as standard (3K on request).

Life: to 95,000 hours.

Options: Available in two sizes with two mounting options - post-top or pendant. Diffuser available in clear, frosted, opal and water droplets finish. Lower cone of light can be coloured.

Manufactured: EU.

Product Compliance: EN 60598; CE.




Pendant with Bracket



Post-Top Version



Pendant with Twin Bracket



DIMENSIONS

All Dimensions in mm.	H	D	Weight	EPA
Size 1	725	640	12kg	0.16m ²
Size 2	1030	900	14kg	0.21m ²

ORDERING CODE

Wattage	Type	Code	Details	Lumens
54w	LED	5FUL11SBA	Fullonia, 350mA, 4K	6895 lm
77w	LED	5FUL12SBA	Fullonia, 500mA, 4K	9355 lm
108w	LED	5FUL13SBA	Fullonia, 700mA, 4K	12310 lm

OPTIONS

RAL: Pls specify

PEN: Pendant mounted