




Seno Spot

Floodlight



Compact sized LED projectors in 3 sizes for accent lighting.

Construction: Die-cast Aluminium with glass lens. IP65. IK06. Stainless Steel (316L) option.

Lens: Tempered Clear Glass lens 4mm.

Installation: Via adjustable U-Bracket. Supplied with pre-wired cable 0.5m long.

Finish: Powder coated polyester. Light Grey RAL 9006 as standard, Dark Grey on request.

LED: 1w - 6w LED, all with remote driver. 4K as standard, 3K available on request. New: 8w Version with Internal Driver.


Options: Stainless steel (316L Grade), DALI, 3K, round or square housing.

Manufactured: EU.


Product Compliance: EN 60598, CE, UKCA.

DIMENSIONS - Round Version


Size 1



Size 2



Size 3




All dimensions in mm.




DIMENSIONS - Square Version


Size 1



Size 2



Size 3



All dimensions in mm.



ORDERING CODE - Aluminium Version

Wattage	Type	Size	Code - Round	Code - Square	Beam	Details	+ Remote Driver	Lumens*
1.5w	LED	1	G1113.BAST400	G1126.BAST400	16°	500mA Driver - Remote**	G-X206	162 lm
1.5w	LED	1	G1113.BAMT400	G1126.BAMT400	32°	500mA Driver - Remote**	G-X206	162 lm
2w	LED	2	G1114.BAST400	G1127.BAST400	8°	700mA Driver - Remote**	G-X624	218 lm
2w	LED	2	G1114.BAMT400	G1127.BAMT400	45°	700mA Driver - Remote**	G-X624	218 lm
3w	LED	3	G1115.BGST400	G1128.BGST400	11°	1050mA Driver - Remote**	G-X210	307 lm
3w	LED	3	G1115.BGMT400	G1128.BGMT400	40°	1050mA Driver - Remote**	G-X210	307 lm
6w	LED	3	G1115.AHMT400	G1128.AHMT400	28°	350mA Driver - Remote**	G-X620	877 lm
6w	LED	3	G1115.AHFT400	G1128.AHFT400	62°	350mA Driver - Remote**	G-X620	877 lm

ORDERING CODE - Stainless Steel Version

1w	LED	1	G1170.BAST400	-	16°	350mA Driver - Remote**	G-X620	116 lm
1w	LED	1	G1170.BAMT400	-	32°	350mA Driver - Remote**	G-X620	116 lm
1.5w	LED	2	G1171.BAST400	-	13°	500mA Driver - Remote**	G-X206	162 lm
1.5w	LED	2	G1171.BAMT400	-	47°	500mA Driver - Remote**	G-X206	162 lm
2w	LED	3	G1172.BAST400	-	10°	700mA Driver - Remote**	G-X624	218 lm
2w	LED	3	G1172.BAMT400	-	37°	700mA Driver - Remote**	G-X624	218 lm

*Source lumens

**Please specify IP20 or IP67 driver required.

OPTIONS

3K: 3000K Colour Temperature

.19: Light Grey Finish

.05: Dark Grey Finish