



## Tri-Series

### Area lighting



Architectural Area Light with symmetric and asymmetric optics.

**Construction:** Aluminium housing. IP66. IK08.

**Lens:** Clear tempered glass as standard. Other types on request.

**Finish:** Black as standard.

**LED:** Available in 40w-100w LED. 4K as standard, 5K on request.

**Driver:** Internal LED driver.

**Options:** DALI, symmetric/asymmetric optics.

**Product Compliance:** EN 60598; CE.



## DIMENSIONS

All dimensions in mm.



450mm Diameter x 526mm Height  
Mast fitter for 60mm or 76mm  
Weight: 10 Kg



## ORDERING CODE

| Wattage | Type | Code      | Description                                | Lumens   |
|---------|------|-----------|--------------------------------------------|----------|
| 40w     | LED  | 5TRI00040 | Tri-Series Area light, Symmetric, 76mm, 4k | 4800 lm  |
| 60w     | LED  | 5TRI00060 | Tri-Series Area light, Symmetric, 76mm, 4k | 7200 lm  |
| 75w     | LED  | 5TRI00070 | Tri-Series Area light, Symmetric, 76mm, 4k | 9000 lm  |
| 100w    | LED  | 5TRI00100 | Tri-Series Area light, Symmetric, 76mm, 4k | 12000 lm |

## OPTIONS

5K: 5000K Colour Temperature

ASY: Asymmetric

60: 60mm Mast fitter

RAL: Please Specify RAL

DALI: Dali