




Conical Pole Series

External lighting



Tapered Conical pole in rooted or flanged version, with optional paint finish. Can be manufactured to client specification and to suit location and/or windage and weight of Luminaire and brackets.

Construction: Galvanised steel construction. Flush Door as standard. C Profile with 2 M6 nuts for Fuse Unit. Optional Spigot sizes, access doors, brackets, etc.

Installation: Rooted as standard (Flanged on request).

Installation: Base details from Veelite. Contractor will supply fuse and internal wiring within pole.

Finish: Galvanised as standard. RAL Finish on request. Wooden Effect on request - see details overleaf.

Product Compliance: EN 40.
Check with Local Authority for compliance if using on Public Roads.



Veelite



ORDERING CODE

Height*	Code	Details
3M	5PBRV0300	Rooted Tapered Conical Column, 76mm Spigot
4M	5PBRV0400	Rooted Tapered Conical Column, 76mm Spigot
5M	5PBRV0500	Rooted Tapered Conical Column, 76mm Spigot
6M	5PBRV0600	Rooted Tapered Conical Column, 76mm Spigot
8M	5PBRV0800	Rooted Tapered Conical Column, 76mm Spigot
10M	5PBRV1000	Rooted Tapered Conical Column, 76mm Spigot
12M	5PBRV1200	Rooted Tapered Conical Column, 76mm Spigot

*Height excludes any Rooted (underground) section.

OPTIONS

RAL: Pls specify
WOD: Wood Effect - pls specify
FLG: Flanged Version
SPG: Pls specify Spigot Size

FLUSH DOOR




WOODEN EFFECT



ELM



KENTUCKY



PINE



WALNUT

This effect is achieved by the application of a Film transfer at 200°C onto the Metal Column. The Photos may not show the colours correctly so sample sections are available. The maximum height of a Column is 8M.

A Photo on the Front Page of this Leaflet shows an 8m Conical Column with Elm Finish.