






Vero Series

External Lighting



Recessed wall light for walkways, pathways, steps, etc. available in 4 versions.

Construction: Die-cast aluminium housing. IP65.

Installation: Separate In-Housing required for Installation.

Lens: Tempered prismatic glass, 3mm.

Finish: Light grey finish as standard. Dark grey on request.

LED: 2.9w -8.7w LED. 4K as standard, 3K on request.

Driver: Internal.

Options: DALI, RAL colours on request.


Manufactured: EU.

Product Compliance: EN 60598, CE.




DIMENSIONS


Size 1




Size 2







Size 3



Size 4



All dimension in mm.



ORDERING CODES

Wattage	Type	Size	Code	Details	+Installation Frame	Lumens*
2.9w	LED	1	G5410.ETXP400	4K, LED Driver Internal	GAC003 (L144 x W87 x D132)	389 lm
8.7w	LED	2	G5406.BRXP400	4K, LED Driver Internal	GAC406 (L226 x W188 x D110)	1167 lm
5.8w	LED	3	G5409.CAXP400	4K, LED Driver Internal	GAC002 (L268 x W144 x D98)	778 lm
8.7w	LED	4	G5408.CAXP400	4K, LED Driver Internal	GAC002 (L268 x W144 x D98)	1167 lm

*Source lumens

OPTIONS

3K: 3000K, Warm White
.05: Dark Grey Finish
.19: Light Grey Finish
DALI: DALI on request